

Job Name:		
Type:		
Part #:		
Notes:		

LSM6

Semi-Recessed MR-16 Emergency Unit

STANDARD









ILLUMINATION

- Two fully adjustable ultra bright, round, 7.0 watt, MR-16 halogen lamp heads standard.
- High performance MR16 halogen lamps with smooth metallized reflector and glass lens for optimal light distribution

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V maintenance-free, rechargeable sealed lead acid battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on the backplate for wall mount.
 Snaps into place making internal electrical connections.
- Knockout for conduit applications.

HOUSING

 Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

ELECTRICAL INFORMATION

INPUT W	ATTS (W)	INPUT AMPS (A)		
120V	277V	120V	277V	
4.2	5.2	0.039	0.021	

ORDERING INFORMATION

MODEL	HOUSIN	HOUSING COLOR		OPTIONS
LSM6	(blank)	White	LED	3.6W High Lumen White LED Lamps
	В	Black	USA	Assembled in USA
		'	PLED	5.0W High Lumen White LED Lamps




- USA: Substantial transformation assembly in the U.S. complies with "Assembled in the USA" under the Buy American Act.
- LED: 3.6W high performance MR-16 base LED Lamps for increased center-to-center spacing.
- PLED: 5.0W high performance MR-16 base LED Lamps for premium center-to-center spacing.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for two years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (20°C 40°C).

DIMENSIONS



Spacing

Mounting Height	8'	10'	12'
LSM6	25'	25'	20'
LSM6-LED	30'	35'	45'
LSM6-PLED	45'	50'	60'