

LSXPEH

EXPLOSIONPROOF LED EMERGENCY LIGHT AND EXIT SIGN

Key Features

- Two high lumen spot lights can be adjusted in horizontal and vertical planes
- Independent battery backup system for exit signs and spotlights
- Unit can power up to two optional remote spot lights
- Field replaceable LED circuit boards and drivers with quick disconnects
- Emergency battery back-up integral to sign (no additional enclosure required)
- 3-hour emergency operation
- Edge-lit sign

Additional Features

- Wall, pendant and end mounting options
- Captive, hinged-access door
- Wide and narrow-beam optics available
- Separate push-to-test and pilot light for local and remote heads
- Separate sealed NiCad batteries for exit sign
- Alternate exit legend and languages available
- Single- or double-sided option
- Three 1" NPT hubs
- Red or green LED options

Standard Materials

Body: A360 aluminum (less than .4% copper content) with baked-on gray epoxy finish

- Gasket: One-piece neoprene
- Sign: Acrylic
- Hardware: Stainless steel



Classifications:

- Class I, Division 1, Groups C & D
- Class II, Division 1, Groups E, F & G
- Class III
- Class I, Zone 1, Groups IIA, IIB
- USCG Regulation 46 CFR Subparts 111.75-15(e) & 112.43
- UL 844 Hazardous Locations
- UL 1598A Marine Outside Type
- UL 1598 Wet Locations
- UL 8750 LED Safety
- UL 924 Emergency Lighting
- CUL
- IP65
- NEMA 4X
- Patent No. 7,287,347; Other Patents Pending




Job Name: _____
 Type: _____
 Part #: _____
 Notes: _____

Certification Guide

LSXPEH Series Emergency Combo with:	Ambient Temperature Range	Class I, Division 1 Groups C & D	Class II, Division 1 Groups E, F & G Class III	Simultaneous Presence Class I & II	UL 1598A Marine	CUL
Green Exit Sign	10° C to 35° C	T6	T6	T6	Yes	Yes
Red Exit Sign	10° C to 45° C	T6	T6	T6	Yes	Yes

LSXPEH - 1 - R - DT - 2 - 2 - XX



1
 SERIES
 LSXPEH LED

2
 NUMBER OF FACES 1 = Single Face
 2 = Double Face

3
 LEGEND COLOR R = Red
 G = Green

4
 VOLTAGE/FREQUENCY DT =
 120/277V 60HZ 24 = 220-240V
50HZ

5
 INSTALLED HEADS
 0 = None
 1 = One
 2 = Two

6
 REMOTE HEADS ¹
 0 = None
 1 = One
 2 = Two
 3 = Three
 4 = Four

7
 OPTIONS ²
 N = Narrow Beam Optics
 W = Wide Beam Optics
 X = EXIT Legend in other languages
 Language must be specified

Combinations Available		
Installed	Remote	Drivers
2	0	1
1	1	1
0	2	1
2	2	2
1	3	2
0	4	2

¹ LSXPEH Series emergency lights with remote head option are provided with extra LED driver. Remote heads can only be wired to the emergency fixtures with remote head option. LED heads are furnished with 1/2"-14 NPT male hub, must be installed on suitably listed explosion proof junction box not provided.

² Consult Factory for pricing.

Part numbering logic is for explaining part number structure only. Not all combinations are possible; consult factory for catalog numbers not listed on chart..