

FEATURES

Lumen Output	1875 to 6250 lumens
Efficacy	125 lm/W
Input Voltage	120-277V
Dimmable	0-10V Continuous
Size	1x4, 2x2, 2x4
CCT	Select (3500K/4000K/5000K/5700K/6500K)
Rating	Damp Location
Warranty	5 Years

APPLICATIONS

Premium indoor luminaire suitable for general indoor commercial spaces, lobbies, offices, meeting rooms, schools, retail stores, restrooms, hallways, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with satin coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltage 120-277V models with 0-10V Continuous Dimming. Tunable 5-CCT (3500K, 4000K, 5000K, 5700K, 6500K) and Tunable 5-Wattages. Operating temperatures -4°F to 113°F (-20°C to 45°C).

MOUNTING

Recessed T-Bar Ceiling Mount.

OPTICS

Anti-UV Frosted Polycarbonate Lens.

EMERGENCY

Installed 90 Minute Emergency Backup Battery Driver options available.

LISTINGS

DLC Premium listed. ETL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

5 year exclusive limited warranty.

LED Center-Basket Troffer

5-Wattages + 5-CCT (35/40/50/57/65K), Damp Rated, 125 lm/W, Dimmable + Smart

Tunable 1x4, 2x2 and 2x4 Models



Emergency Driver



TUNABLE CORRELATED COLOR TEMPERATURES (CCT)

3500K 4000K 5000K 5700K 6500K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 5-Wattages (40W Max, 50W Max)
Power Factor: >0.9
Total Harmonic Distortion (THD): <15%
Operating Temperature: -4°F to 113°F (-20°C to 45°C)

LIGHTING DATA

Lumens: 1875 to 6250
Lumens Per Watt: 125 lm/W
Correlated Color Temperature (CCT): 5-CCT (35K, 40K, 50K, 57K, 65K)
Dimmable: 0-10V
Color Rendering Index (CRI): 83
L70: 50000 hours

ORDERING INFORMATION

Model	Size	Wattage	Voltage	Current	Lumens	Efficacy	CCT	Dimming	Color	Dimensions
HTRF14-TCP40W-CCT	1x4	(15W, 20W, 25W, 30W, 40W)	120-277V	0.14A@120V, 0.06A@277V 0.18A@120V, 0.08A@277V 0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V	1875 2500 3125 3750 5000	125 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	47.60"L x 11.89"W x 2.76"H
HTRF22-TCP40W-CCT	2x2	(15W, 20W, 25W, 30W, 40W)	120-277V	0.14A@120V, 0.06A@277V 0.18A@120V, 0.08A@277V 0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.37A@120V, 0.16A@277V	1875 2500 3125 3750 5000	125 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	23.78"L x 23.78"W x 2.76"H
HTRF24-TCP50W-CCT	2x4	(25W, 30W, 35W, 40W, 50W)	120-277V	0.23A@120V, 0.10A@277V 0.28A@120V, 0.12A@277V 0.32A@120V, 0.14A@277V 0.37A@120V, 0.16A@277V 0.47A@120V, 0.20A@277V	3125 3750 4375 5000 6250	125 lm/W	(3500K, 4000K, 5000K, 5700K, 6500K)	0-10V	White	47.60"L x 23.78"W x 2.76"H

Emergency


EM8 (BLD-YT08H-XXX) [INSTALLED] Slim Emergency Backup LED Driver, 8W, 90-Min Battery

EM20 (BLD-HM20D-YYY) [INSTALLED] Emergency Backup LED Driver, 20W, 90-Min Battery (≤100W Luminaires)

PHYSICAL DIMENSIONS


1x4 Models

47.6"L x 11.89"W x 2.76"H



2x2 Models

23.78"L x 23.78"W x 2.76"H



2x4 Models

47.6"L x 23.78"W x 2.76"H

